

The Refresher - Propane Polisher, Stripper, Buffer, & Sander



Features:

- Rugged all steel construction
- Planetary drive to eliminate shadowing and side torque
- Sealed planetary drive with synchronous belt to eliminate slip and increase durability
- Premium bearings and bearing seals throughout for durability
- Standard dust control functionality
- Standard 8 gallon water tank
- Premium German centrifugal clutch
- Adaptor port for active vacuum
- Locking easy spin-on spin-off heads for quick application change
- 330lbs head pressure
- Includes 3 sets quick change heads for stripping, polishing, and burnishing concrete
- Compatible for use with 4" ceramic or resin diamond pucks and diamond impregnated pads
- Transport wheel for easy loading and maneuvering
- Low profile - fits under 8" shelf
- Green certifications: EPA, CARB, LEED, CE, & GS-42

Refresher Specifications

| | |
|-------------------------------|--|
| Path Size | 30" (76 cm) |
| Engine | Kawasaki 603 cc |
| Centrifugal Clutch | Standard |
| Head Pressure | 330 lbs (150 kg) |
| Head Size | 3 ea. 10" (25 cm) Quick Change Heads |
| Head Speed (Clockwise) | 1295 RPM |
| Brush Drive Speed (Clockwise) | 250 RPM |
| Machine Weight | 495 lbs (225 kg) |
| Height | 42.25" (107 cm) |
| Length | 47.25" (120 cm) |
| Width | 32.75" (83 cm) |
| Shipping Weight* | Approx. 535 lbs (243 kg) |
| Machine Warranty | 1 Year |
| Engine Warranty | 2 Years / 500 Hours |
| Green Certifications | EPA, CARB, LEED, GS-42 Available with Blue Sky Certified Engine |

Included Drive Heads:

- 3 x 10" Malgrit Strip Brush
- 3 x 10" Mighty Lok
- 3 x 10" Velcro Hook & Loop

Safety Specifications:

- Meets US Green Building Council LEED IAQ
- Credit 3.4 Requirements
- CE, CARB, EPA & GS-42 Compliant
- Low Oil Shutdown
- Safety Regulator Fuel System

Available Options:

- Auto Emissions Shut Down
- Blue Sky Certified Engine
- Kill Switch Lanyard



800-331-1423 www.aztecproducts.com